PORTWEST.



CE EN 397: 2012 + A1:2012

MANUFACTURER

PORTWEST, IDA Business Park, Westport, Co. Mayo, Ireland

Name and address of the Notified Body having issued EU certificate INSPEC INTERNATIONAL ID - NOTIFIED BODY NUMBER 0194 56 LESLIE HOUGH WAY, SALFORD, GREATER MANCHESTER, M66AJ, UK Models :: P563-Height Endurance Helmet Vented

EN SAFETY HELMETS USER INSTRUCTION

Complies with the requirements of Regulation (EU 2016/425) and the general requirments of the standard EN397:2012+A1:2012

This PPE is intended to be used as to protect the users against falling objects and consequential brain injury and skull fracture. This helmet shell of the head potection is designed for protecting the users from 1) thrown object from above the head; 2) falling object; 3) impacts at very Low temperature (-30%). Do not use this helmet for dimbing activities, fine-fighting activities and sporting activities. USAGE OF THE POTECTIVE FLEMET:

For adequate protection this helmet must fit or be adjusted to the size of the user's head.

Use the back-wheel knob to adjust to the appropriate size: Turn right to close / adjust smaller size; Turn left to open / adjust bigger size.

The helmet's in made to aboot the energy of a blow by partial destruction or damage to the shell and the harness, and even though such damage may not be readily apparent, and helmet subjected to severe impact should be replaced. The attention of users is also drawn to the dange of modifying or removing any of the original component parts of the helmet, other than as recommended by the helmet manufacture. Helmets should not be adapted for the purpose of fitting attachments in any way not recommended by the helmet manufacture.

Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the helmet manufacturer.

AFTER USE:

if the helmet becomes dirty or contaminated, particularly on the external surface, it should be carefully cleaned in accordance with cleaning recommendations below (maintenance/storage). We highlight the potential risk of loss of protection in case of inappropriate cleaning and ageing of the helmet.

ADJUSTMENT AND INSPECTION OF THE PROTECTIVE HELMET

In order to ensure effective protection, this helmet should be own with its peak forward is in in straight position) and it should be adjusted to the user's head size (not fin to loose or to squeeze) by its adjustenet system knoeld at the rear of the helmet. The helmet file is affected by several factors, such as cold, heat, chemical products, sun light or misuse. Daily and before any use a check should be performed in order to identify any sign of rendering (racks, flaws) the helmet. Its hareas and accession's flagible. Any helmet having been subject to a strong shock or having were signs should be replaced. If thas no defaults, it is therefore proper for the intended use. The manufacturing date is marked inside each helmet. The manufacturing date.

MAINTENANCE / STORAGE

This protective helmet may be cleaned and disinfected by means of a doth impregnated in a low concentration deaning solution. You use any abasive or corrossive chemical product. If this helmet cannot be cleaned by using this method, it should be replaced. The product must be transported its packaging that protects the product from shock, exposure to moisture, thermain hazards, exposure to light, holding it away from any product or material or substance that can deteriorate it.

When it is not used anymore or during transportation, the hearts should be stored in a dy could place away from light, fost and in a location granting that no chemical product or sharp object bends it by failing above. It should not be compressed or stored dose to any source of heat. It is recommended that the storage temperature is kept in the range 20-15°C. This heart does not induce any substance known to be susceptible of causing allergies. However if a sensitive person has an allergic reaction, it should therefore leave the hazardous area, remove the helmet and ask for medical advice.

ATTENTION:

Missing or deficiently respect of instructions of use, adjustment/inspections and maintenance/storage, may limit effectiveness of insulation protection.

SPARE PARTS:

The following spare parts are made available from the manufacturer

 -4 points chin strap (ref. style code: PA49 – Chin Strap 4 Endurance Height)

-Sweat Band (ref. style code PA45 – Sweat Band Endurance)

MARKINGS:

FORTWEST Manufacturer Identification

C E = Markings indicating compliance with the health and safety requirements of Regulation (EU) 2016/425

EN397:2012+A1:2012 =referring standard and year of publication

plastic recycling symbol

ABS = symbol of the material of the shell

(on the example:2018/March)

MARKING (FACULTATIVE TESTING)

Helmets bearing one of the following markings meet the additional requirements as below: $-30^{\circ}C / -20^{\circ}C$ Very low temperature The helmet keeps its performance

above these temperatures

Download declaration of conformity @ www.portwest.com/declarations