

A145 - Cold Grip Glove

Collection: Thermal Protection Gloves

Range: Hand Protection

Materials: Latex, Acrylic, Elastane, Polyester

Dipping:

Inner Pack: 12

Outer Carton: 120

Product information

Specially designed for use in cold conditions. The crinkled latex finish offers excellent grip and the warm acrylic 7 gauge liner provides level 2 contact cold protection against cold hazards.

Thermal Protection Gloves

When cold thermal hazards are present, the hands' motor skills can be greatly reduced, this leads to increased risk of accidents and injury. Specially designed thermal protective gloves are available to combat these dangers in hazardous environments.

Hand Protection

A wide and increasing range of hand protection products is available. In order to help cater to every need. Only the best materials and manufacturing methods are used in the production of Portwests' extensive range of Hand Protection products....

Standards

EN ISO 21420: 2020 Dexterity 4

EN 388: 2016 + A1: 2018 (2231X)

EN 511: 2006 (X2X)

ANSI/ISEA 105: 2016 CUT Level (A2)



Features

- Specially designed for use in cold conditions
- Warm 7 gauge acrylic liner for extreme cold protection
- Crinkle latex grip offers excellent grip
- Palm dipped to increase dexterity and ventilation
- Fully dipped thumb for increased coverage
- Breathable seamless liner
- CE certified
- UKCA marked
- Retail tag which aids presentation for retail sales
- Robust 7 gauge liner



PRODUCT SPECIFICATION & TECHNICAL DATA

A145 - Cold Grip Glove

Commodity Code: 6116102091

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)

Bracetown Business Park

D15 YN2P, Ireland

Cert No: 2777/14834-01/E00-00

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
A145OBLM	Orange/Blue	65.0	30.0	50.0	0.1360	0.0975	5036108180264	15036108603630
A145OBLL	Orange/Blue	65.0	30.0	50.0	0.1360	0.0975	5036108180257	15036108603623
A145OBLXL	Orange/Blue	65.0	30.0	50.0	0.1440	0.0975	5036108180288	15036108603647
A145OBLXXL	Orange/Blue	65.0	30.0	50.0	0.1600	0.0975	5036108180295	15036108692191