

## NLG Tether Loop™, 150 Product Code: 101381

Max Load: 3 KG / 6.6 LBS



#### **OVERVIEW**

Tether Loops™ are a simple easy-to-install solution to create a secure tether point on tools with a captive hole such as a hammer, saw or spanner. Consisting of a tough steel core with an anti-puncture sleeve they are perfect for harsh and dirty work environments.

#### **VIEW ONLINE**

https://neverletgo.com/products/tether-loop-1 50/



## NLG **ID**<sup>™</sup> Serialised and safe

Simply scan the NLG ID tag with your phone to instantly access certificates, instruction videos and log inspections. (See Specification if included).



# Third-party tested and certified

Independent laboratory load testing certificates and Declarations of Conformity are available on request. Please contact team@neverletgo.com.

NEVERLETGO.COM 1

DESCRIPTION	Tether Loops™ create a rapid tether point suitable for any tool with a captive hole or handle – or even a shaped tool. So whether it's a hammer, saw or spanner, Tether Loops™ are effortless to self-install anywhere at any time. With its specially developed one-way thread and Lock Alert™ indicator for checking it is correctly installed, Tether Loops™ are a simple and time-saving method of creating an attachment point that is approved and third-party tested. Each Tether Loop™ comes with its own unique serial number. A tough aircraft-grade steel core with an extended thread mechanism ensures a fail-safe attachment point for tools up to 3kg in weight.  Tether Loops™ are available in three sizes making them ideal for a wide range of tools.	
FEATURES	Fast and easy installation with secure locking thumb screw Clever one-way thread and Lock Alert™ help ensure it's secure and correctly installed Tough aircraft-grade steel core Anti-puncture, abrasion-resistant PU protective sleeve makes maintenance effortless Comes in three sizes	
TECHNICAL SPECIFICATION	Max Load: 3 KG / 6.6 LBS Safety Standards: ANSI/ISEA 121-2018, CE / UKCA, NS 9611:2022+AC Load Tested and Third-party Certified: Dynamic (2:1 Safety Factor) NLG ID™ Technology / Scannable Compatible Unique Serial Number Dimensions: 150mm Max Lanyard Length: 200 CM / 78 IN	
RETAIL	EAN (GTIN-13) 5060572180086	UNIT WEIGHT (G) 5
SHIPPING	HS CODE 7326.90.9890	COUNTRY OF ORIGIN Taiwan

NEVERLETGO.COM 2



### Tether Loop™, 150

Product Code: 101381

View online

https://neverletgo.com/products/tether-loop-150/

Learn more about:
Dropped object prevention
Tool tethering
Tool lanyards

Useful resources: Tool Box Tool Tether Guide Library

CONTACT	+44 (0)330 016 0030 neverletgo.com
INSPECTION	In addition to routine checks before each use, all equipment should undergo regular detailed inspections, conducted and recorded by a competent person using the NLG Inspection Checklist. If any part is worn or shows signs of degradation, immediately retire from service. In the event of a drop, quarantine the equipment for a thorough inspection.
	© Click to download Inspection Checklist
LEGAL	NLG makes every effort to ensure the information in this Datasheet is accurate and current. However, NLG reserves the right to change the product specification when necessary. NLG cannot be held responsible for any inaccuracies or omissions.  Copyright © 2023. NLG ® and Never Let Go ® are registered trademarks.

NEVERLETGO.COM 3