

Lift RES-Q



Length:	CE	Weight:
40 m		6.47 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

Lift Res-Q is the perfect device for lifting and rescue operations. Made of aluminium alloy and high-strength steel and dia. 9.6 mm semi static kernmantle rope assembled with the device.

Rope ends with double figure of 8 knots for connection with karabiner. Provided with 3 hooks ref. FA 50 220 21.

- **Controlled descent speed:** 0,8 m / sec regardless the weight (max. weight 225kg).
- **Maximum descent height:** 300 m.
- **Maximum lifting height:** 300 m.
- **Usable with electric screwdriver:** For high ascents.
- **Brake system:** Automatic and redundant.
- **Maximum no. of users:** 2 users < 225 kg.
- **Inspection:** Once a year or every 6000 m of rope.

Available in 2 different lengths: 20 m (FA 70 201 20), 40 m (FA 70 201 40).

For specific lengths, you need to associate the following references:

- FA 70 201 00: device only.

- FA 70 009 99: Kernmantle rope per meter.

- FA 70 009 98: Required length of rope with double "figure of 8" knots and automatic locking hook at one end.

Conformity: EN 341:2011-1A, EN 1496 :2007 B.

Material of components:

Rope: polyamide diam. 9,6 mm (EN 1891-A)

Device: aluminium alloy and high-strength steel

HS CODE**CARTON SIZE / PIECES****AET N°2013-3938 / EMZ****AUVA-STP N° 0511**

Adalbert-Stifter Straße 65
1200 Vienna, Austria

Module C2, 2016/425 UE Regulation**AUVA-STP N° 0511**

Adalbert-Stifter Straße 65
1200 Vienna, Austria